

ML4342-V4 Series

34 ~ 50 Watt
(1-10 Dimmable)

1-10 Dimmable

Features

- Universal AC Input (100-240Vac)
- Constant Current Mode for LED Lamp
- Output Current Adjustable by Inside VR
- 2 Output terminal for Fluorescence Type LED Lamp (max 2 terminals)
- Standard Output Connector used for easy DC wiring
- 1-10 Dimming compatible
- Flicker Free



Marks



Image



Specification

| Model | Rated Power | Input | PF ¹⁾ | Output ²⁾ | EFFY ¹⁾ | Withstand Isolation | THD | Dimming | Approvals |
|---------------------------|--|------------------------|------------------|----------------------|--------------------|---|------|--------------------|-------------|
| ML5342-V4 | 53 W | 100-240Vac 47~63 Hz | >0.94 | 38-42Vdc | >85% | 3 KV (I/P to O/P) > 100MΩ @500VDC) | <20% | 1-10 ³⁾ | CE, PSE, KS |
| ML4342-V4 | 43 W | | | | | | | | CE, PSE, KS |
| ML3442-V4 | 34 W | | | | | | | | CE, PSE, KS |
| Note | 1) PF/Efficiency are measured at max. load condition 2) Output current is factory set 3) Minimum dimming level : 20% | | | | | | | | |

ML4342-V4 Series

Mechanical Dimension (mm)

1-10 Dimmable

